diskontcomputer.com
Firma Matzner Michael e.U.
Traunuferstrasse 110
4052 Ansfelden, Austria

SwifTouch™ Digital Photo Frame

Hidden control buttons illuminate in blue when touched to indicate your selection and direct you to your photo, slideshow, music or video.

Photo mode touch controls activated.

Touch controls not activated.

Main menu

Photo thumbnails

Normal view

16x zoom

USB 2.0 port allows for fast photo imports from your camera, computer or thumb drive.

Also supports memory cards: SD, SDHC, MMC, MS, MS Pro, XD, CF (I)

Video and audio capabilities for a personalized viewing experience.

Customizable slideshows.

Create and edit your personal slideshows with amazing effects, such as, fade, shutter, cross comb, mask brick, dissolve, bar and random.

MODEL NO.		VFD725W	VFM735W	DPG807BK
LCD	Type	7" TFT LCD	7" TFT LCD	8" TFT LCD
	Effective Viewing Area	152.4(W)x91.44(H)mm	152.4(W)x91.44(H)mm	162(W)x121.5(H)mm
	Resolution	800x480	800x480	800x600
	Contrast Ratio	500:1 (typ), 400:1(min)	500:1 (typ), 400:1(min)	500:1 (typ), 400:1(min)
	Viewing Angles	140° horizontal, 120° vertical	140° horizontal, 120° vertical	140° horizontal, 120° vertical
	Brightness	200 cd/m^2 (typ)	200 cd/m^2 (typ)	200 cd/m^2 (typ)
	Aspect Ratio	5 :3	5 : 3	4 : 3
COMPATIBILITY	Card Reader	CF (Type I), SD, SDHC, MMC, XD, MS, MS Pro	CF (Type I), SD, SDHC, MMC, XD, MS, MS Pro	CF (Type I), SD, SDHC, MMC, XD, MS, MS Pro
	Photo Formats	JPEG	JPEG	JPEG
	Video Formats	N/A	MP3, MPEG1(.dat/.mpeg/ .mpg), MPEG4(.avi)	MP3, MPEG1(.dat/.mpeg/ .mpg), MPEG4(.avi)
	USB	USB 2.0	USB 2.0	USB 2.0
MEMORY		N/A	2GB	2GB
AUDIO	Speaker	N/A	2x1.5 watt	2x1.5 watt
POWER	Voltage	100-240 VAC,50/60Hz (Auto Switching)	100-240 VAC,50/60Hz (Auto Switching)	100-240 VAC,50/60Hz (Auto Switching)
	Consumption	9 W(Max)	10.5 W(Max)	10.5 W(Max)
DIMENSIONS	Physical (WxHxD)	210x160x28.6mm	210x160x28.6mm	216x182x28.3mm
WEIGHT		440 g	453.2 g	614 g
REGULATIONS		FCC, cUL(adapter only),CE	FCC, cUL(adapter only),CE	FCC, cUL(adapter only),CE
PACKAGES CONTENTS		Digital Photo Frame, Power Adapter, Quick Start Guide, User Guide, USB cable	Digital Photo Frame, Power Adapter, Quick Start Guide, User Guide, USB cable	Digital Photo Frame, Power Adapter, Quick Start Guide, User Guide, USB cable

ISO 9001:2000 FM 40187 ISO 14001:1996 FM 40968

ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

Specifications subject to change without notice. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2008 ViewSonic Corporation. All rights reserved. [14172-00B-09/08] DPG807BK-1

ViewSonic See the difference

For more product information, visit us on the web at ViewSonic.com